

# 85123-SU



LFX/MWP/MW/SCT/ORB/PC

LED Mini Wall Pack Outdoor Fixture, Power Selectable 8W/10W/15W/25W, 3500 Lmns, Color Selectable 30K/40K/50K, Dimmable, D2D Photocell, ETL Listed, Bronze, Residential, Commercial



Project: \_\_\_\_\_  
Type: \_\_\_\_\_  
Catalog #: \_\_\_\_\_  
Date: \_\_\_\_\_  
Comments: \_\_\_\_\_

## Technical Specifications

### Photometrics

Lumen	1160/1450/2175/3625
Emitted Color	CCT Selectable
Color Temp	30K/40K/50K
Color Rendering Index (CRI)	70+
Beam Spread	120°
Lifespan	50000

### Electrical

Watt	8/10/15/25
Input Voltage	120-277
Power Factor	0.92
Dimmable	0-10V Low Voltage

### Ratings / Certifications

Safety Certification	ETL Listed - Wet Location
Operating Temperature	-40°F - 104°F
Warranty	5 Years

### Construction

Fixture Material	Aluminum & Polycarbonate
Fixture Finish	Bronze
Lens Material	Polycarbonate
Lens Finish	Frosted
Shape	
Mounting	Wall
Usage	Outdoor

