

Sunlite 85281 2-Foot LED Linear High Bay Light Fixture, 165 Watts, 23000 Lumens, 120-277V, 5000K Super White, Dimmable, UL Listed, Polycarbonate Diffuser Lens, White, For Commercial & Residential Use

Linear

DESCRIPTION:

Sunlite's 2-Foot LED Linear High Bay Light Fixtures offers a durable aluminum body that has a 50,000-hour lifespan, 23000-lumen output at 165 watts, and 5000K super white color temperature. Featuring a glare-reducing lens, it's dimmable with 0-10V control. Suspension chain included. Ideal for indoor industrial use, it's UL and DLC Listed, suitable for damp locations, and measures 23.98" L x 11.97" W x 1.57" H.



FEATURES:

- **PREMIUM CONSTRUCTION** - Made from high-quality aluminum, this fixture offers exceptional heat dissipation and durability, ensuring long-lasting performance and a sleek appearance. The polycarbonate diffuser lens provides uniform light distribution, minimizes glare, and delivers impact resistance, making this fixture suitable for a wide range of applications.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Estimated annual energy costs of \$19.87 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time.
- **SUPER WHITE LIGHT** - Color temperature is 5000K super white light with a bright 23000-lumen output while only using 165 watts of electricity.
- **DIMMABLE** - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control.
- *Sunlite's 2-Foot LED Linear High Bay Light Fixtures offers a durable aluminum body that has a 50,000-hour lifespan, 23000-lumen output at 165 watts, and 5000K super white color temperature. Featuring a glare-reducing lens, it's dimmable with 0-10V control. Suspension chain included. Ideal for indoor industrial use, it's UL and DLC Listed, suitable for damp locations, and measures 23.98" L x 11.97" W x 1.57" H.*

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	0-100%
Material	Aluminum
Lens Material	Polycarbonate
Lens Finish	Clear

Electrical Characteristics

Watts	165
Volts	120-277
LED Chip Manufacturer	SMD2835
Power Factor	.9
Temperature	-22°F~122°F

Light Characteristics

Lumens Brightness	23000
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	90°
Flicker	<30%

Fixture Characteristics

Style	Industrial
Shape	Linear
Mounting	Pendant
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Classification	Premium

Product Dimensions

Size	24"
Item Dimension (in)	(W) 11.97 (H) 1.57 (D) 23.98

Product Data

Pack Size	2
Item UPC	653703852812
Warranty Years	5

ACCESSORIES:

Catalog # 89699-SU
MS/LFX/HB/V2

Catalog # 89785-SU
RC/LFX/HB