

Sunlite 85514 LED Flood Light Outdoor Fixture, 50 Watts, 6250 Lumens, Selectable 30K/40K/50K Color, Dimmable, UL listed, 100-277V, Bronze, For Residential & Commercial Use

DESCRIPTION:

The Sunlite LED Outdoor Commercial flood lights are the ideal replacement light for traditional streetlights. Equivalent to 150 watts, our area lights combine visual consistency, energy efficiency LEDs, long-term reliability, and rugged durability. With these remarkable qualities, our fixtures are built to last for many years to come. Best for parking lots, streets, floods, and many other outdoor areas. Remarkable for entrance lighting, courtyard lighting, industrial lighting, garage lighting, security lighting, and many more. Fixture Dimensions: 8.5" H x 6.12" W x 1.93" D.

FEATURES:

- **FOR LARGE AREAS** – The Sunlite LED commercial area lights are ideal for traditional streetlights using Metal Halide bulbs or HPS fixtures. Equivalent to 150 watts, our area lights combine optical consistency, energy-efficient LEDs, and long-term reliability. This flood light can be used in areas that need a lot of illumination. Best for parking lots, streets, flood, and many other outdoor areas.
- **DURABILITY** – Built to last and withstand harsh environments, our outdoor wall packs are constructed of a rugged die-cast aluminum housing that is completely sealed and corrosion-resistant. The low profile and lightweight, compact design help keep water and environmental dust-out. With a rating of IP65 water-resistant, the area lights can withstand wet environments and challenging weather conditions.
- **MANY APPLICATIONS** – With dimming capabilities (0-10V), 100v-277 LED Driver, adjustable color temperature; the outdoor area lights can work well in many applications. With its bright LEDs and its high lumen output of 6250, our lights are great for entrance lighting, courtyard lighting, industrial lighting, garage lighting, security lighting, and many more.
- **ADJUSTABLE COLOR TEMPERATURE** - Test different color temperatures before installation and never be dissatisfied with CCT again. This simplistic fixture has adjustable LED color-changing technology (3000K, 4000K, 5000K), quickly meeting different demands in areas. With a simple switch inside the fixture, the color temperature is adjusted to your desire. **PLEASE NOTE:** select the desired color temperature before completely mounting the fixture. (Instructions included).
- **EASY INSTALLATION & UL LISTED** – The LED wall flood light arrives with preconfigured screw mounts for easy installation. Compatible with Knuckle mounts, Trunion mounts, and Yoke mounts. Tested to meet UL's rigorous

SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|-------------------|
| Average Rated Hours | 50000 |
| Finish | Bronze |
| Average Life Span Years | 46 |
| Dimmable | Yes |
| Dimming Type | 0-10V Low Voltage |
| Dimming Percentage | 0-100% |
| Material | die-casting |
| Lens Finish | Clear |
| Application | Outdoor |

Product Dimensions

| | |
|-------------------------------|---------------------------|
| Item Dimension (in) | (W) 6.12 (H) 8.5 (D) 1.93 |
| Package Dimension (in) | (W) 11.5 (H) 13.31 (D) 3 |
| Package Weight (lb) | 3.97 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 6 |
| Item UPC | 653703855141 |
| Warranty Years | 5 |

Electrical Characteristics

| | |
|------------------------------|---------------|
| Watts | 50 |
| Volts | 120-277 |
| LED Chip Manufacturer | Seoul 3030 |
| Power Factor | 0.92 |
| Temperature | -40°F - 122°F |

Light Characteristics

| | |
|----------------------------------|----------------|
| Lumens Brightness | 6250 |
| Color Rendering Index CRI | 80 |
| Emitted Color | CCT Selectable |
| Color Temperature Kelvin | 30K/40K/50K |
| Beam Angle | 7H x 7V |

Fixture Characteristics

| | |
|---------------------------|-----------|
| Shape | Rectangle |
| Number of Lights | 1 |
| Mounting | Pole |
| Fixture Technology | LED |
| Use Location | Outdoor |

Additional Features

| | |
|--------------------------------|--------------------------|
| Safety Rating Mark | UL Listed - Wet Location |
| Safety Rated For Canada | Yes |
| Safety Rated For USA | Yes |
| DLC | Yes |
| DLC Number | S-BVKSJ8 |
| DLC Classification | Premium |
| Mercury Free | Yes |

ACCESSORIES:

Catalog # 85522-SU
TRUNION

Catalog # 85518-SU
KNUCKLE

Catalog # 85495-SU
LFX/FL/MW/SCT/PC