

Sunlite 85531 2-Foot LED Linear High Bay Fixtures with Acrylic Diffuser Lens, 85 Watts, Multi-Volt, 11560 Lumens, 5000K Daylight, 80 CRI, Dimmable, UL Listed, White, For Commercial & Residential Use

Linear

DESCRIPTION:

The 2-Foot LED Linear High Bay Fixtures with Acrylic Diffuser Lens from Sunlite are an energy efficient solution to your industrial lighting needs. Color temperature is 5000K Daylight with a bright 11560-lumen output while only using 85 watts of electricity. A long, 50,000-hour lifespan means years of reliable and maintenance free service with no bulbs to replace. Estimated annual energy costs of \$10.24 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time. These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10%. 80 CRI. UL Listed for damp location installation. DLC Listed for design and quality. Designed for indoor use only. For use on 120/277-volt electrical systems. High lumen output designed for use in warehouses, commercial garages, workshops, factories, or any indoor industrial environment. Dimension: 12.99" W x 23.82" H x 3.64" D.

FEATURES:

- **UPGRADE TO LED** - Replace older high bay lights with energy efficient LEDs. These 2-Foot linear fixtures feature a durable and lightweight steel body designed for pendant mounting finished in white. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Daylight with a bright 11560-lumen output while only using 85 watts of electricity.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance free service with no bulbs to replace. Estimated annual energy costs of \$10.24 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time.
- **DIMMABLE** - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10% with 80 CRI.
- **UL LISTED** - UL Listed for damp location installation. DLC Listed for design and quality. Designed for indoor use only. For use on 120/277-volt electrical systems. High lumen output designed for use in warehouses, commercial garages, workshops, factories, or any indoor industrial environment. Dimension: 12.99" W x 23.82" H x 3.64" D.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Material	Steel & Acrylic
Lens Finish	White

Electrical Characteristics

Watts	85
Volts	100-277

Light Characteristics

Lumens Brightness	11560
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K

Fixture Characteristics

Shape	Linear
Number of Lights	1
Mounting	Pendant
Fixture Technology	LED
Use Location	Indoor

Product Dimensions

Size	24"
Item Dimension (in)	(W) 12.99 (H) 23.82 (D) 4
Item Weight (lb)	6.4
Package Dimension (in)	(W) 24.75 (H) 13.48 (D) 4
Package Weight (lb)	6.4

Product Data

Item UPC	653703855318
Warranty Years	5

ACCESSORIES:

Catalog # 30574-SU
Surface