

Sunlite 85544 2x4 Foot LED White Backlit Panel Fixture, White Diffuser, Power Selectable 30W/40W/50W, Color Selectable 35K/40K/50K, Dimmable, 80 CRI, UL Listed, Commercial, Residential Use, 4 Pack



DESCRIPTION:

Sunlite LED White Backlit Panel Fixture are a long life, energy efficient replacement for fluorescent fixtures. LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. Designed for installation into 2 X 4-foot drop ceiling grids. These fixtures allow you to choose the color temperature at the time of installation Select 3500K Neutral White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 30 watts, 40 watts, or 50 watts. These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control and its backlit feature for more even light distribution. Provides up to 50,000 hours energy efficient light. No maintenance, long-life LED technology means you won't need to climb ladders to replace difficult to reach bulbs. Estimated annual energy costs of \$3.61/\$4.82/6.02 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time. UL Listed for safety and quality. DLC listed for design and efficiency. Great for commercial or residential applications on 120–277-volt service. Dimension: 47.80" W x 1.38" H x 23.82" D.

FEATURES:

- **ULTRA SLIM DESIGN** - LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. Designed for installation into 2 X 4-foot drop ceiling grids.
- **COLOR & POWER SELECTABLE** - These fixtures allow you to choose the color temperature at the time of installation Select 3500K Neutral White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 30 watts, 40 watts, or 50 watts.
- **DIMMABLE & BACKLIT** - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control and it's backlit for more even light distribution than edge lit.
- **LONG LIFE LED** - Provides up to 50,000 hours energy efficient light. No maintenance, long-life LED technology means you won't need to climb ladders to replace difficult to reach bulbs. Estimated annual energy costs of \$3.61/\$4.82/6.02 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time.
- **UL LISTED** - UL Listed for safety and quality. DLC listed for design and efficiency. Great for commercial or residential applications on 120–277-volt service. Dimension: 47.80" W

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Material	Metal & PS
Lens Finish	Frosted

Electrical Characteristics

Watts	30/40/50
Volts	120-277
Equivalent Wattage	6
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	—20 —40

Light Characteristics

Lumens Brightness	3300/4400/5500
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	110°
Flicker	Ripple current<10%

Fixture Characteristics

Mounting	Recessed
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PCATO8G2
DLC Classification	Standard

Product Dimensions

Size	2X4
MOL (in)	1.38"
Item Dimension (in)	(W) 47.8 (H) 1.38 (D) 23.82
Package Dimension (in)	(W) 48.5 (H) 24.5 (D) 6.62
Package Weight (lb)	38.59

Product Data

Pack Size	4
Warranty Years	5

ACCESSORIES:

Catalog # 90487-SU
LFX/2X4/B-L/MW/EM/MS/SCT

Catalog # 90488-SU
LFX/2X4/B-L/MW/MS

Catalog # 90713-SU
LFX/2X4/B-L/MW/EM/SCT

Catalog # 88171-SU
Emergency

Catalog # 85145-SU
LFX/FLAT/2X4

Catalog # 85149-SU
LFX/FLAT/2X4