

ST Series

Sunlite 87913 LED T8 U-Bend Tube Light Bulb (Type A+B), 15 Watts (32W=), 120-277V, 1900 Lumens, Medium 2-Pin G13 Base, Plug & Play or Ballast Bypass, UL Listed, Color Tunable 35K/40K/50K, Pack of 12

Hybrid Type A + B

DESCRIPTION:

Sunlite's T8 U-Bend Tube Light Bulb is a high-quality, energy-efficient replacement for your existing T8 fluorescent tube. These non-dimmable bulbs have a 1900-lumen output and let you pick the color temperature within the tube bulb, you can choose between 3500K Neutral White, 4000K Cool White or even 5000K Daylight depending on your preferences. Its unique design is compatible with most U-bend fixtures and requires no additional hardware. This tube type is an A+B or universal hybrid design, which means that it can be installed through a plug & play or with a ballast bypass (Instructions Included). The 2-pin G13 base allows easy replacement of your existing fluorescent tubes without changing the wiring or ballasts. Long life LED technology means up to 50,000 hours of reliable service while only using 42 watts of electricity so there is no need to replace difficult to access bulbs less often. UL Listed for damp location. Shatterproof PET coating for safety.



FEATURES:

- **COLOR TUNABLE** – These non-dimmable bulbs have a 1900-lumen output and let you pick the color temperature within the tube bulb, you can choose between 3500K Neutral White, 4000K Cool White or even 5000K Daylight depending on your preferences.
- **EASY INSTALLATION** - Its unique design is compatible with most U-bend fixtures and requires no additional hardware. This tube type is an A+B or universal hybrid design, which means that it can be installed used as plug & play or with a ballast bypass (Instructions Included).
- **MEDIUM 2-PIN BASE** – The 2-pin G13 base allows easy replacement of your existing fluorescent u-bend tubes without changing the wiring or ballasts.
- **LONG LIFE** - Long life LED technology means up to 50,000 hours of reliable service while only using 42 watts of electricity so there is no need to replace difficult to access bulbs less often.
- **UL LISTED** – UL Listed for damp location. This can be used in a variety of settings, including office buildings, schools, and retail spaces. Shatterproof PET coating for safety.

SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	50000
Finish	Frosted
Base	Medium 2-Pin (G13)
Average Life Span Years	46
Dimmable	No
Material	Glass

Electrical Characteristics

Amps	0.013
Watts	15
Volts	120-277
Equivalent Wattage	FB32T8
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	1900
Color Rendering Index CRI	83
Coating	PET Coating
Emitted Color	CCT Tunable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	320°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
Mercury Free	Yes

Product Dimensions

Size	6"
Item Dimension (in)	(W) 7.2 (H) 1.3 (D) 23.2
Package Dimension (in)	(W) 15.2 (H) 8.7 (D) 24
Package Weight (lb)	11.75

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703879130
Warranty Years	5