

T Series**Sunlite 88043 2FT LED T8 Glass Tube Bulb (Type A+B), 10W, 120-277V, 1450 Lm, Medium 2-Pin G13 Base, Single Or Double-Ended Ballast, UL Listed, 25 Pack, CCT Switch 35K/40K/50K, F17T8/F24T8 Replacement**

Hybrid Type A + B

DESCRIPTION:

Discover Sunlite's innovative T8 LED bulb, featuring adjustable color temperature (3500K, 4000K, or 5000K) with a built-in switch, and a versatile Type A+B design for compatibility with electronic ballasts or direct AC power. The easy-to-install medium 2-Pin G13 Base suits various applications, including commercial and industrial spaces. Compatible with both instant-start and programmed-start ballasts, enjoy up to 50,000 hours of energy-efficient lighting with just 10 watts of power. UL Listed for damp locations, this multi-volt (120-277) bulb ensures safety and quality in diverse settings. Bulb Dimension 1.4" H x 1.4" W x 24" D.

FEATURES:

- **COLOR SELECTABLE** – This bulb allows you to choose the color temperature at any time. Select 3500K, 4000K or even 5000K depending on your preference using a switch located on the bulb.
- **EASY INSTALLATION** – With its Type A+B design of the bulb, it can be used with either electronic ballasts (Type A) or directly wired to AC power (Type B), making it an ideal choice for retrofitting existing bulbs or for new installations. Its medium 2-Pin G13 Base feature makes it easy to install in a variety of applications, including commercial and industrial spaces, warehouses, offices, and more.
- **SINGLE OR DOUBLE ENDED BALLAST** - The single ended ballast feature is compatible with instant-start ballasts, while the double ended ballast option can work with both instant-start and programmed-start ballasts. This allows you to choose the most convenient and cost-effective option for your space.
- **LONG LIFE LED** - Long life LED technology means up to 50,000 hours of reliable service while only using 10 watts of electricity, so there is no need to replace difficult to access bulbs less often.
- **UL LISTED** – UL Listed for damp location. Tested for safety and quality that can be used in various settings, including office buildings, schools, and retail spaces. Multi-volt 120-277. Bulb Dimension 1.4" H x 1.4" W x 24" D.

SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|--------------------|
| Bulb Shape | Linear Tube |
| Average Rated Hours | 50000 |
| Finish | Frosted |
| Base | Medium 2-Pin (G13) |
| Average Life Span Years | 46 |
| Dimmable | No |
| Material | Glass |

Electrical Characteristics

| | |
|------------------------------|--------------|
| Watts | 10 |
| Volts | 120-277 |
| Equivalent Wattage | F17T8, F24T8 |
| LED Chip Manufacturer | SMD2835 |
| Temperature | -4°F - 113°F |

Light Characteristics

| | |
|----------------------------------|----------------|
| Lumens Brightness | 1450 |
| Color Rendering Index CRI | 83 |
| Coating | Powder Coating |
| Emitted Color | CCT Tunable |
| Color Temperature Kelvin | 35K/40K/50K |
| Beam Angle | 320° |

Additional Features

| | |
|--------------------------------|---------------------------|
| Safety Rating Mark | UL Listed - Damp Location |
| Safety Rated For Canada | Yes |
| Safety Rated For USA | Yes |
| DLC | Yes |
| DLC Number | S-93ANTC |
| DLC Classification | Standard |
| Mercury Free | Yes |

Product Dimensions

| | |
|----------------------------|------------------------|
| Size | 2' |
| Item Dimension (in) | (W) 1.4 (H) 1.4 (D) 24 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 25 |
| Pack Size | 1 |
| Item UPC | 653703880433 |
| Warranty Years | 5 |