

ST Series

Sunlite LED T5 Plug and Play 25W Light Bulb (G5) Base, Super White

Plug and Play

DESCRIPTION:

Sunlite Lighting's LED T5 lamps deliver a comfortable but vivid and flicker-free ray of light to any setting. Consuming only 25 watts of energy to produce a stunning 5000K Super White light in addition to offering significant energy savings when compared to competing bulbs. Ideal for various settings while not utilizing any hazardous chemicals, such as Mercury. Featuring a (G5) base, they are designed to fit in a variety of applications. With an average lamp life of 50000 hours, Sunlite Lighting's T5 bulbs do more than just illuminate a room; these bulbs add a layer of life to any and all dÃ©cor. Warning Before installing, be sure to confirm this T8 Plug & Play lamp is compatible with your ballast. The Ballast Compatibility List can be found on www.sunlite.com under the specific Item Number. Make sure the lighting fixture is wired correctly per the ballast or lamp instructions. Never install or remove the T8 lamp with the lighting fixture energized, or arcing at the pins may occur. Sunshine Lighting assumes no liability for incidental or consequential damages resulting from the misuse of this product.

FEATURES:

- Produces An Efficient 5000K Super White Beam Of Light For All Your Ceiling Fixtures And More
- On Average, These Light Bulbs Last An Astonishing 50000 Hours
- First-Class Plug And Play Tube Lighting That Consumes 25 Watts Of Energy; Replaces Standard Linear Fluorescent Light Bulbs
- 4 Foot Tubular LED Plug And Play Bulb Perfect For Your Bathroom, Hallway, And/Or Office's Compatible Ceiling Light Fixtures
- High-Quality, UL Listed, Modern Replacement LED Light Bulbs Sold At A Highly Competitive Price



SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|-----------------------|
| Bulb Shape | T5 |
| Average Rated Hours | 50000 |
| Finish | White |
| Base | Miniature Bi-Pin (G5) |
| Average Life Span Years | 46 |
| Dimmable | No |
| Material | Glass |

Electrical Characteristics

| | |
|------------------------------|---------------------------|
| Watts | 25 |
| Equivalent Wattage | F54T5/HO |
| LED Chip Manufacturer | 2835 |
| Power Factor | 0.9 |
| Temperature | -20° to 45° |
| Ballast Factor | High Output (HO) Required |

Light Characteristics

| | |
|----------------------------------|-------------|
| Lumens Brightness | 3200 |
| Color Rendering Index CRI | 82 |
| Emitted Color | Super White |
| Color Temperature Kelvin | 5000K |
| Beam Angle | 180° |

Additional Features

| | |
|-----------------------------------|---------------------------|
| Safety Rating Mark | UL Listed - Damp Location |
| UL Rated Enclosed Fixtures | Yes |
| DLC | Yes |
| DLC Number | PL3OND2LNN12 |
| DLC Classification | Standard |

Product Dimensions

| | |
|-------------------------------|----------------------------|
| Size | 4 Foot |
| MOL (in) | 45.8 |
| Diameter (in) | 0.64 |
| Item Dimension (in) | (W) 0.62 (H) 45.8 (D) 0.62 |
| Package Dimension (in) | (W) 45.5 (H) 0.62 (D) 0.62 |
| Package Weight (lb) | 0.300 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 25 |
| Pack Size | 1 |
| Item UPC | 653703882307 |
| Warranty Years | 5 |
| Package Type | Sleeve |