

Catalog # 88275-SU PLD/LED/9W/IS/50K/V2

Plug-In

Sunlite 88275-SU LED PLD Light Bulb, 9 Watts (26W Equivalent), 1000 Lumens, G24q Base, Ballast Dependant, CFL Replacement, UL Listed, 50K - Super White 1 Pack

Plug and Play

DESCRIPTION:

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 1000 lumen with 5000K color temperature at 5000K. Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.

FEATURES:

- UPGRADE TO LED Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage.
- NO FLICKERING OR BUZZING LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 1000 lumen with Super White color temperature at 5000K.
- ENERGY EFFICIENT These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. That's a 65% energy savings. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- LONG LIFE SPAN Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- A SAFER CHOICE Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.





sunlite

SPECIFICATIONS:

General Characteristics

Prod	uct	Dime	ensio	ns
1100	uci	Dille	11310	13

Bulb Shape	PLD	MOL (in)	6.57
Average Rated Hours	50000	Item Dimension (in)	(W) 1.4 (H) 6.61 (D) 1.4
Finish	White	Item Weight (Ib)	0.170
Base	4-Pin (G24q)	Package Dimension (in)	(W) 1.42 (H) 6.76 (D) 1.4
Average Life Span Years	46	Package Weight (lb)	0.210
Dimmable	No		
		Product Data	

Electrical Characteristics

Watts	9	Pack Size
Equivalent Wattage	18	Item UPC
Temperature	-4°F - 113°F	Warranty Years

1100 82

Super White 5000K

Light Characteristics

Lumens Brightness		
Color Rendering Index CRI		
Emitted Color		
Color Temperature Kelvin		

Additional Features

Safety Rating Mark DLC DLC Number **DLC Classification**

UL Listed - Damp Location Yes PL41RZW4HKS3 Standard

4 .44

Case Unit Rate	12
Pack Size	1
Item UPC	653703882758
Warranty Years	5
Package Type	Box