

Plug-In**Sunlite 88298-SU LED PLD Ballast Bypass Light Bulb, 9.5 Watts (26W Equivalent), G24q Base, CFL Replacement, UL Listed, 50K - Super White 1 Pack**

Bypass

DESCRIPTION:

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9.5 watt LED ballast bypass bulbs from Sunlite. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 900 lumen with Super White color temperature at 5000K. Provides up to 50,000 hours of energy efficient light so you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation. These 4-Pin base (G24q) bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs.

FEATURES:

- **UPGRADE TO LED** - Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9.5 watt LED ballast bypass bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. They feature a 4-Pin base (G24q) and a 270 degree beam angle that can be rotated at the base for optimal coverage.
- **ENERGY EFFICIENT** - These 9.5 watt LED bulbs are direct replacements for 26 watt CFL bulb. Low annual operating costs of only \$1.14. (Based on 3 Hours/Day at \$0.11/kWh)
- **LONG LIFE SPAN** - Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- **A SAFER CHOICE**: Unlike cfl bulbs these led lamps contain no hazardous chemicals and are UL listed for damp location installation
- **BALLAST BYPASS REQUIRED** - These fluorescent replacement LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions available online or consult an electrician for more information.



SPECIFICATIONS:

General Characteristics

Bulb Shape	PLD
Average Rated Hours	50000
Finish	White
Base	2-Pin LED Base (G24d)
Average Life Span Years	46
Dimmable	No
Material	Plastic

Electrical Characteristics

Watts	9
Volts	120-277
Equivalent Wattage	18
LED Chip Manufacturer	Type A
Power Factor	0.9
Temperature	-20-45°

Light Characteristics

Lumens Brightness	1000
Color Rendering Index CRI	82
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	160°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes

Product Dimensions

MOL (in)	6.65
Diameter (in)	1.1
Item Dimension (in)	(W) 1.4 (H) 6.61 (D) 1.39
Item Weight (lb)	0.190
Package Dimension (in)	(W) 1.5 (H) 6.75 (D) 1.5
Package Weight (lb)	0.230

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703882987
Warranty Years	5
Package Type	Box