

ED Series**Sunlite 03625-SU LU70/MOG 70 Watt
High Pressure Sodium Light Bulb, Mogul
Base (E39), ANSI Code S62, 6300 Lumen,
24000 Life Hours, Clear, 2100K**

High Pressure Sodium

DESCRIPTION:

Sunlite High Pressure Sodium lamps are a long-life replacement for your existing HID fixtures. This 70 watt bulb puts out a bright 6300 lumens of light. It features a mogul base (E39) and long 24000 hour average lifespan. Standard ED23 bulb shape with clear finish. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code S62. Bulb measurements 2.949 inches diameter, 6.903 inches tall.

FEATURES:

- **HIGH PRESSURE SODIUM** - Sunlite High Pressure Sodium lamps are a long-life replacement for your existing HID fixtures. Standard ED23 shape.
- **HIGH INTENSITY DISCHARGE** - This 70 watt bulb puts out a bright 6300 lumens of light. Color temperature is 2100K. Clear glass bulb.
- **MOGUL BASE** - Standard mogul base (E39). Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.949 inches diameter, 6.903 inches tall.
- **LONG LIFE** - This bulb features a long 24000 hour average lifespan.
- **ANSI CODE S62** - This HPS bulb is for use in S62 ballast fixtures.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED23
Ansi code	S62
Average Rated Hours	24000
Finish	Clear
Base	Mogul Screw (E39)
Average Life Span Years	22

Electrical Characteristics

Watts	70
-------	----

Light Characteristics

Lumens Brightness	6300
Color Rendering Index CRI	24
Color Temperature Kelvin	2100K

Product Dimensions

MOL (in)	6.903
Diameter (in)	2.949"
Item Dimension (in)	(W) 2.95 (H) 6.9 (D) 2.95
Package Dimension (in)	(W) 3.2 (H) 7.8 (D) 3.2
Package Weight (lb)	0.400

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036250
Warranty Years	2

VARIATIONS:



03625-SU



03630-SU



03635-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Hours	Pack
03625-SU	LU70	70	6300	24	2100K 24000	1
03630-SU	LU100	100	8500	24	2100K 20000	1
03635-SU	LU150	150	16000	24	2100K 20000	1