

## ST Series

### Bypass Dual End

#### **DESCRIPTION:**

*Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.*

#### **FEATURES:**

- 
- 
- 
- 
-

## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	T8
<b>Average Rated Hours</b>	50000
<b>Finish</b>	White
<b>Base</b>	Medium 2-Pin (G13)
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	No
<b>Material</b>	Glass

### Electrical Characteristics

<b>Watts</b>	9
<b>Volts</b>	120-277
<b>Equivalent Wattage</b>	F17T8, F20T12
<b>Power Factor</b>	0.9
<b>Temperature</b>	-20° to 45°

### Light Characteristics

<b>Lumens Brightness</b>	1150
<b>Color Rendering Index CRI</b>	82
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K

### Additional Features

<b>Safety Rating Mark</b>	UL Classified - Damp Location
<b>UL Rated Enclosed Fixtures</b>	Yes
<b>DLC</b>	Yes
<b>DLC Number</b>	PLHMAW8P16WQ
<b>DLC Classification</b>	Standard

### Product Dimensions

<b>Size</b>	2 Foot
<b>MOL (in)</b>	23.22
<b>Diameter (in)</b>	0.98
<b>Package Dimension (in)</b>	(W) 23.75 (H) 1.02 (D) 1.02
<b>Package Weight (lb)</b>	0.240

### Product Data

<b>Case Unit Rate</b>	25
<b>Pack Size</b>	1
<b>Item UPC</b>	653703884325
<b>Warranty Years</b>	5
<b>Package Type</b>	Sleeve