

ED Series

Sunlite 03637-SU MH50/U/MED M110 Metal Halide Lamp, 50 Watts, Pulse Start, Medium Base (E26), ED17, 10,000 Hours Life, 3400 Lumen, Clear Finish, 4000K

Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 50 watt metal halide bulbs have a bright 3400 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 10,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code M110. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.195 inches in diameter, 5.257 inches tall.

FEATURES:

- METAL HALIDE Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- HIGH INTENSITY DISCHARGE This 50 watt bulb puts out a bright 3400 lumens of light. Color temperature is 4000K. Clear glass bulb.
- MEDIUM BASE Standard medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.195 inches diameter, 5.257 inches tall.
- PULSE START These bulbs feature pulse start for quicker startup, less lumen depreciation, long 10,000 hour average lifespan, and more lumens per watt so you save energy.
- ANSI CODE M110 This metal halide bulb is for use in M110 ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.





SPECIFICATIONS:

General Characteristics

Bulb Shape Ansi code Average Rated Hours **Finish** Base

Average Life Span Years

Electrical Characteristics

Light Characteristics

Watts

Lumens Brightness Color Rendering Index CRI

Coating **Emitted Color** Color Temperature Kelvin

ED17 M110 10000 Clear

Medium Screw (E26)

9

50

3400

Uncoated

Cool White

4000K

65

Light Center Length

MOL (in)

Product Dimensions

Diameter (in) Item Dimension (in) Package Dimension (in)

Package Weight (lb)

Case Unit Rate Pack Size Item UPC Warranty Years 5.257

2.13" 2.195"

(W) 2.19 (H) 5.26 (D) 2.19

(W) 2.4 (H) 6 (D) 2.5

0.150

Product Data

12 1

653703036373

1