

#### ED Series

### Sunlite 03638-SU MP175/U/PS M110/O Protected Metal Halide Lamp, 50 Watts, Medium Base (E26), Pulse Start, ED17, 10,000 Hours Life, 3200 Lumen, Clear Finish, 4000K

Protected Metal Halide

#### DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. Energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 50 watt protected pulse start metal halide bulbs have a bright 3200 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 10,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, wall packs, and other commercial and industrial lighting applications. ANSI Code M110/O. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.119 inches in diameter, 5.286 inches tall.



#### FEATURES:

- **PROTECTED METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 50 watt bulb puts out a bright 3200 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MEDIUM BASE** - Larger medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.119 inches diameter, 5.286 inches tall.
- **PULSE START** - These protected pulse start bulbs feature a long 10,000 hour average lifespan.
- **ANSI CODE M110/O** - This metal halide bulb is for use in M110/O ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.

SPECIFICATIONS:

General Characteristics

Bulb Shape	ED17
Ansi code	M110/O
Average Rated Hours	10000
Finish	Clear
Base	Medium Screw (E26)
Average Life Span Years	9

Electrical Characteristics

Watts	50
-------	----

Light Characteristics

Lumens Brightness	3200
Color Rendering Index CRI	65
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Product Dimensions

MOL (in)	5.286
Light Center Length	3.375"
Diameter (in)	2.119"
Item Dimension (in)	(W) 2.12 (H) 5.29 (D) 2.12
Package Dimension (in)	(W) 2.3 (H) 6 (D) 2.4
Package Weight (lb)	0.250

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036380
Warranty Years	1