

### Plug-In

Sunlite LED PLD Plug & Play Light Bulb, 11 Watts (18 Watts Equiv.), 1025 Lumens, Color Selectable 30K/40K/50K, G24q 4-Pin Base, 180 Degree Beam Angle, UL Listed, RoHS Compliant, 1 Pack

Plug and Play

# **DESCRIPTION:**

Discover the innovative Sunlite's PLD Plug-In By-Pass Light Bulb, designed for efficient light distribution and easy installation in tight spaces. With a life span of up to 50,000 hours each bulb puts out a bright 1025 lumens of light while only using 11 watts of electricity. Annual energy costs are a low \$1.32 (Based on 3 hours/day at \$0.11/kWh). This bulb has a 4-Pin G24q base allowing for an easy, secure fit into compatible fixtures. With multiple color temperature options you can choose between 3000K Warm White, 4000K Cool White and 5000K Daylight. UL Listed for damp location and for totally enclosed fixtures. They are also ROHS Certified, unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.

# FEATURES:

- UPGRADE TO LED Replace your inefficient fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Can be used in enclosed fixtures and has a High Color Rendering Index rating of 80.
- G24Q BASE This bulb has a 4-Pin G24q base allowing for an easy, secure fit into compatible fixtures.
- ENERGY EFFICIENT With a life span of up to 50,000 hours each bulb puts out a bright 1025 lumens of light while only using 11 watts of electricity. Annual energy costs are a low \$1.32 (Based on 3 hours/day at \$0.11/kWh).
- COLOR SELECTABLE With multiple color temperature options you can choose between 3000K Warm White, 4000K Cool White and 5000K Daylight. Changing ambience for any application is now easy with just the slide of a switch.
- UL LISTED AND ROHS COMPLIANT UL Listed for damp location and for totally enclosed fixtures. They are also ROHS Certified, unlike fluorescent bulbs, they contain no harmful chemicals and do not require special handling or disposal.

# sunlite

# **SPECIFICATIONS:**

## **General Characteristics**

Bulb Shape	PLD	MOL (in)	5.86
Average Rated Hours	50000	Diameter (in)	1.61
Finish	White	Item Dimension (in)	(W) 5.86 (H) 1.61 (D) 1.22
Base	4-Pin (G24q)	Package Dimension (in)	(W) 6.38 (H) 1.71 (D) 1.35
Average Life Span Years	46	Package Weight (lb)	0.221
Dimmable	No		
Material	PC & Aluminum	Product Data	
		Case Unit Rate	12
Electrical Characteristics		Pack Size	1

## **Electrical Characteristics**

Watts	11
Volts	Plug & Play
Equivalent Wattage	18
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-4°F - 113°F

# **Light Characteristics**

Lumens Brightness	1025
Color Rendering Index CRI	80
Emitted Color	CCT Tunable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	180°
Flicker	Yes

# **Additional Features**

Safety Rating Mark UL Rated Enclosed Fixtures Yes **Rohs Compliant** Yes

UL Listed - Damp Location

12
1
653703888040
5
Box

# **Product Dimensions**

Item UPC

Warranty Years

Package Type