

**Sunlite 89782 LED Commercial UFO High Bay Light Fixture, 200 Watts (400W=), 28000 Lumens, 5000K Super White, Dimmable, UL Listed, Black, 120-277V, IP65, For Warehouses, Factories & Workshops**

UFO

**DESCRIPTION:**

Upgrade to energy-efficient lighting with Sunlite's sleek, UFO-style high bay fixture, featuring a durable, lightweight die-cast aluminum body for optimal heat dissipation. Enjoy 28,000 lumens of 5000K Super White light while consuming only 200 watts, resulting in significant energy savings. With a 50,000-hour lifespan, 500 built-in LEDs, and 0-10V dimmability, experience reliable, maintenance-free lighting in commercial spaces such as warehouses, workshops, and retail areas. UL Listed for wet locations and IP65 rated, this fixture is suitable for 120-277-volt electrical systems and includes a 39.6" AC cord. Dimensions: 12.6" D x 5" H.

**FEATURES:**

- **UPGRADE TO LED** - Replace older high bay lights with energy-efficient LEDs. These UFO-style fixtures feature a durable and lightweight die-cast aluminum body designed for pendant mounting that provides optimal heat dissipation. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Super White with a bright 28000-lumen output while only using 200 watts of electricity. Each fixture has 500 built-in LEDs.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Benefit from significant energy savings over time.
- **DIMMABLE LED** - The fixture can be dimmed (0-10V Dimmable) when installed with an LED-compatible dimmer.
- **UL LISTED** - UL Listed for wet location installation. High lumen output is designed in warehouses, commercial garages, workshops, factories, retail spaces, or any commercial environment. IP65 Rated. For use on 120-277-volt electrical systems. Includes 39.6" AC cord. Fixture Dimensions: 12.6 D x 5" H.



**SPECIFICATIONS:**

**General Characteristics**

<b>Average Rated Hours</b>	50000
<b>Finish</b>	Black
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	Yes
<b>Dimming Type</b>	0-10V Low Voltage
<b>Dimming Percentage</b>	10-100%
<b>Material</b>	Aluminum
<b>Lens Material</b>	Polycarbonate
<b>Lens Finish</b>	Clear

**Product Dimensions**

<b>MOL (in)</b>	12.6
<b>Diameter (in)</b>	5
<b>Item Dimension (in)</b>	(W) 12.6 (H) 5 (D) 12.6
<b>Cord Length</b>	40"

**Product Data**

<b>Item UPC</b>	653703897820
<b>Warranty Years</b>	5

**Electrical Characteristics**

<b>Watts</b>	200
<b>Volts</b>	120-277
<b>LED Chip Manufacturer</b>	SMD2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	-4°F - 122°

**Light Characteristics**

<b>Lumens Brightness</b>	28000
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K
<b>Beam Angle</b>	90°

**Fixture Characteristics**

<b>Mounting</b>	Pendant
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Indoor

**Additional Features**

<b>Safety Rating Mark</b>	UL Listed - Wet Location
<b>DLC Classification</b>	Premium
<b>Mercury Free</b>	Yes
<b>CE Certified</b>	Yes

**ACCESSORIES:**

Catalog # 89699-SU  
MS/LFX/HB/V2

Catalog # 89785-SU  
RC/LFX/HB

Catalog # 89787-SU  
PCR/LFX/HB/V2

Catalog # 89788-SU-DEACT  
AR/LFX/HB

Catalog # 89789-SU  
PCL/LFX/HB/V2

Catalog # 89790-SU  
SC/LFX/HB