

## Sunlite LED Commercial UFO High Bay Light Fixture, 300 Watts (750W Equiv.), 39000 Lumens, 5000K Super White, Dimmable, UL Listed, Black, 120-277V, IP65, For Warehouses, Factories & Workshops

UFO

### DESCRIPTION:

Upgrade to energy-efficient lighting with Sunlite's sleek, UFO-style high bay fixture, featuring a durable, lightweight die-cast aluminum body for optimal heat dissipation. Enjoy 39000 lumens of 5000K Super White light while consuming only 300 watts, resulting in significant energy savings. With a 50,000-hour lifespan, 375 built-in LEDs, and 0-10V dimmability, experience reliable, maintenance-free lighting in commercial spaces such as warehouses, workshops, and retail areas. UL Listed for wet locations and IP65 rated, this fixture is suitable for 120-277-volt electrical systems and includes a 39.6" AC cord. Fixture Dimensions: 12.32 D x 4.53" H.

### FEATURES:

- **UPGRADE TO LED** - Replace older high bay lights with energy-efficient LEDs. These UFO-style fixtures feature a durable and lightweight die-cast aluminum body designed for pendant mounting that provides optimal heat dissipation. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Super White with a bright 39000-lumen output while only using 300 watts of electricity. Each fixture has 375 built-in LEDs with a beam angle of 120 degrees.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance-free service with no bulbs to replace. Benefit from significant energy savings over time.
- **DIMMABLE LED** - The fixture can be dimmed (0-10V Dimmable) when installed with an LED-compatible dimmer.
- **UL LISTED** - UL Listed for wet location installation. High lumen output is designed in warehouses, commercial garages, workshops, factories, retail spaces, or any commercial environment. IP65 Rated. For use on 120-277-volt electrical systems. Includes 39.6" AC cord. Fixture Dimensions: 12.32 D x 4.53" H.



## SPECIFICATIONS:

### General Characteristics

<b>Average Rated Hours</b>	50000
<b>Finish</b>	Black
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	Yes
<b>Dimming Type</b>	0-10V Low Voltage
<b>Material</b>	Aluminum
<b>Lens Material</b>	Polycarbonate
<b>Lens Finish</b>	Clear

### Product Dimensions

<b>Cord Length</b>	39.6"
--------------------	-------

### Product Data

<b>Item UPC</b>	653703897844
<b>Warranty Years</b>	5

### Electrical Characteristics

<b>Watts</b>	300
<b>Volts</b>	120-277
<b>LED Chip Manufacturer</b>	SMD2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	-40°F - 122°F

### Light Characteristics

<b>Lumens Brightness</b>	39000
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K
<b>Beam Angle</b>	90°

### Fixture Characteristics

<b>Shape</b>	UFO
<b>Mounting</b>	Pendant
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Indoor

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Wet Location
<b>DLC</b>	Yes
<b>DLC Number</b>	S-XSJ2W6
<b>DLC Classification</b>	Premium
<b>Mercury Free</b>	Yes
<b>CE Certified</b>	Yes

## **ACCESSORIES:**

Catalog # 89785-SU  
RC/LFX/HB

Catalog # 89699-SU  
MS/LFX/HB/V2

Catalog # 89786-CMP  
Screw