

08564-SU



LFX/MWP/MW/SCT/ORB/PC/G3

Mini Wall Pack Outdoor Fixture 15W/20W/30W 30K/40K/50K  
Dimmable 120-277V + Photocell Oil Rubbed Bronze



Project: \_\_\_\_\_  
Type: \_\_\_\_\_  
Catalog #: \_\_\_\_\_  
Date: \_\_\_\_\_  
Comments: \_\_\_\_\_

Technical Specifications

Photometrics

|                             |                |
|-----------------------------|----------------|
| Lumen                       | 2100/2800/4200 |
| Emitted Color               | CCT Selectable |
| Color Temp                  | 30K/40K/50K    |
| Color Rendering Index (CRI) | 80             |
| Beam Spread                 | 180°           |
| Lifespan                    | 50000          |

Electrical

|               |          |
|---------------|----------|
| Watt          | 15/20/30 |
| Input Voltage | 120-277  |
| Power Factor  | 0.9      |
| Dimmable      | TRUE     |

Ratings / Certifications

|                       |                          |
|-----------------------|--------------------------|
| Safety Certification  | UL Listed - Wet Location |
| Operating Temperature | -40°F - 104°F            |
| Warranty              | 5 Years                  |

Construction

|                  |                   |
|------------------|-------------------|
| Fixture Material | Die-Cast Aluminum |
| Fixture Finish   | Bronze            |
| Lens Material    | Polycarbonate     |
| Lens Finish      | Clear             |
| Shape            | Rectangular       |
| Mounting         | Wall              |
| Usage            | Outdoor           |