

## A Series

### Appliance

#### **DESCRIPTION:**

*Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.*

#### **FEATURES:**

- 
- 
- 
- 
- 



## SPECIFICATIONS:

### General Characteristics

|                                |                                       |
|--------------------------------|---------------------------------------|
| <b>Bulb Shape</b>              | A15                                   |
| <b>Average Rated Hours</b>     | 15000                                 |
| <b>Finish</b>                  | White                                 |
| <b>Base</b>                    | Intermediate Screw (E17)              |
| <b>Average Life Span Years</b> | 14                                    |
| <b>Dimmable</b>                | Yes                                   |
| <b>Dimming Type</b>            | Forward Phase (Triac or Incandescent) |
| <b>Material</b>                | Aluminum + Plastic                    |

### Product Dimensions

|                      |      |
|----------------------|------|
| <b>MOL (in)</b>      | 3.49 |
| <b>Diameter (in)</b> | 1.89 |

### Product Data

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 12           |
| <b>Pack Size</b>      | 6            |
| <b>Item UPC</b>       | 653703414096 |
| <b>Warranty Years</b> | 3            |
| <b>Package Type</b>   | Box          |

### Electrical Characteristics

|                              |              |
|------------------------------|--------------|
| <b>Amps</b>                  | 0.080        |
| <b>Watts</b>                 | 6            |
| <b>Volts</b>                 | 120          |
| <b>Equivalent Wattage</b>    | 40           |
| <b>LED Chip Manufacturer</b> | SMD2835      |
| <b>Power Factor</b>          | 0.7          |
| <b>Temperature</b>           | -4°F - 113°F |

### Light Characteristics

|                                  |            |
|----------------------------------|------------|
| <b>Lumens Brightness</b>         | 480        |
| <b>Color Rendering Index CRI</b> | 80         |
| <b>Emitted Color</b>             | Warm White |
| <b>Color Temperature Kelvin</b>  | 3000K      |
| <b>Beam Angle</b>                | 230°       |
| <b>Beam Angle Description</b>    | Omni       |

### Additional Features

|                                |   |
|--------------------------------|---|
| <b>Safety Rating Mark</b>      | ETL - Damp Location                     |
| <b>Safety Rated For Canada</b> | Yes                                     |
| <b>Safety Rated For USA</b>    | Yes                                     |
| <b>Title 20</b>                | Not for sale in the State of California |
| <b>Mercury Free</b>            | Yes                                     |